

Wilson Company Filter Build Program

Low Pressure Filters

Model	Max Flow GPM (LPM)	Max Pressure PSI (bar)	Mounting Style
12AT	17 (64)	150 (10.3)	Spin-On
50AT	50 (190)	150 (10.3)	Spin-On
PT2/PT4	50 (190)	150 (10.3)	Tank Top
Moduflow Plus	150 (581)	200 (13.8)	Inline, In-Tank
RF4	150 (581)	150 (10.3)	Return, In-Tank



Medium Pressure Filters

Model	Max Flow GPM (LPM)	Max Pressure PSI (bar)	Mounting Style
12CS	XX (X)	500 (34.5)	In-Line
50CS	50 (190)	500 (34.5)	In-Line
15CN	25 (94)	1000 (69)	In-Line
40CN	80 (302)	1000 (69)	In-Line
80CN	120 (452)	1000 (69)	In-Line
IL8	425 (1609)	500 (34.5)	In-Line, Duplex, Quadplex



High Pressure Filters

Model	Max Flow GPM (LPM)	Max Pressure PSI (bar)	Mounting Style
15P	20 (75)	3000 (207)	In-Line, Manifold
30P	45 (170)	3000 (207)	In-Line, Manifold
30PD	25 (94)	3000 (207)	In-Line, Manifold
WPF1	10 (40)	7000 (483)	In-Line
WPF2	26 (100)	7000 (483)	In-Line, Manifold
WPF3	42 (160)	7000 (483)	In-Line
WPF4	95 (360)	7000 (483)	In-Line, Manifold
WPF5	137 (520)	7000 (483)	In-Line, Manifold



- Hydraulic Filter Elements Available in 2, 5, 10, and 20 Micron
- 48 Hour Delivery for Filter Assembly Orders of 3 Pieces or Less

